



MATERIAL SAFETY DATA SHEET

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Manufacturer: FC PRO, LLC
Address: 19914 G.H. Circle
Waller, TX 77484, U.S.A.
(863) 294-8483 (9:00 A.M. to 5:00 P.M. Eastern)
(863) 294-7783 (fax)
Email: info@fcprosolutions.com
Website: www.fcprosolutions.com

**For emergencies, call Chemtrec anytime at 1-800-424-9300.
Outside US, call Chemtrec Collect at 703-527-3887.**

Product Name: FC-PRO Xylene Replacement
Product Code: 971084
Issue Date: February 15, 2011

Section 2: HAZARDS IDENTIFICATION

Emergency Overview

Appearance/Odor: Pale yellow to amber liquid with terpene odor.

Product is Combustible.

Slippery when spilled.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Eye contact, skin contact, inhalation.

Eye: Causes moderate to severe irritation.

Skin: May cause slight redness. Prolonged or repeated exposure may cause drying of the skin.

Inhalation: May cause nose, throat, and respiratory tract irritation, coughing, headache.

Ingestion: Not likely to be toxic, but may cause vomiting, headache, or other medical problems.

Medical Conditions Aggravated By Exposure: May irritate the skin of people with pre-existing skin conditions.

This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC, ACGIH or NTP.

OSHA Regulatory Status

This material is combustible, which is defined as having a flash point between 100°F (37.8°C) and 200°F (93.3°C). Combustible materials are hazardous according to the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Component</u>	<u>CAS #</u>	<u>% by Wt.</u>
Terpene Hydrocarbons	68956-56-9	100

Section 4: FIRST AID MEASURES

Eye Contact: Remove contact lenses at once. Flush with water for at least 15 minutes. If irritation persists, seek medical attention.

Skin Contact: Wash affected area with copious amounts of soap and water. If irritation develops, seek medical attention.

Material Safety Data Sheet

FC-PRO Xylene Replacement

Inhalation: If symptoms of overexposure are experienced, move to fresh air. If symptoms persist, seek medical attention.

Ingestion: Seek medical attention immediately. DO NOT induce vomiting. Rinse mouth with water. DO NOT administer anything by mouth to an unconscious person. DO NOT leave victim unattended.

General: As with any chemical, employees should thoroughly wash hands with soap and water after handling this material.

Section 5: FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Carbon dioxide, foam or dry chemical. Caution: Carbon dioxide will displace air in confined spaces and may create an oxygen deficient atmosphere.

Unsuitable Extinguishing Media: Water.

Products of Combustion: Forms acrid fumes, carbon monoxide, and carbon dioxide.

Protection of Firefighters: Vapors may be irritating to eyes, skin and respiratory tract. Firefighters should wear self-contained breathing apparatus (SCBA) and full fire-fighting turnout gear.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Product is slippery when spilled. Isolate the hazard area. Deny entry to unnecessary and unprotected personnel.

Environmental Precautions: Keep out of drains, sewers, ditches and waterways.

Methods for Containment: Dike spill area and cap leaking containers as necessary to prevent further spreading of spilled material. Absorb spilled liquid with suitable material such as dirt or sand.

Methods for Clean Up: Eliminate all ignition sources. Use equipment rated for use around combustible materials. Oil soaked rags may spontaneously combust; place in appropriate disposal container.

Other Information: There are no special reporting requirements for spills of this material.

Section 7: HANDLING AND STORAGE

Handling

Keep away from heat, sparks and flame. Open container slowly to release pressure caused by temperature variations. Do not allow this material to come in contact with eyes. Avoid prolonged contact with skin. Use in well-ventilated areas. Do not breathe vapors. Drum lining may occasionally chip and fall to the bottom of container; product should be filtered or strained before blending or repackaging. As with any chemical, employees should thoroughly wash hands with soap and water after handling this material.

Storage

Product may be packaged in phenolic-lined steel containers or fluorinated plastic containers. Store in well-ventilated area with proper sprinkler/fire deterrent system. Storage temperature should not exceed the flash point for extended periods of time. Keep container closed when not in use. Air should be excluded from partially-filled containers by displacing with nitrogen or carbon dioxide. Do not cut, drill, grind or weld on or near this container; residual vapors may ignite.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Engineering Controls: Provide ventilation. Keep away from sparks and flames.

Eye/Face Protection: Wear safety glasses or goggles.

Skin Protection: Nitrile gloves are recommended. Boots, apron, or bodysuit should be worn as necessary.

Respiratory Protection: Not normally required. If adequate ventilation is unavailable, use NIOSH approved air-purifying respirator with organic vapor cartridge or canister.

Material Safety Data Sheet

FC-PRO Xylene Replacement

General Hygiene Considerations: Wash hands thoroughly after handling. Have eyewash and emergency shower facilities immediately available. Launder contaminated clothing before reuse.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Color: Yellow to amber.

Odor: Terpene odor.

Physical State: Liquid.

Flash Point: 120°F (49°C)

Solubility in Water: Insoluble

Note: These specifications represent a typical sample of this product, but actual values may vary. Certificates of Analysis and Specification Sheets are available upon request.

Section 10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Keep away from heat, sparks and flames.

Incompatible Materials: Strong oxidizing agents and strong acids, including acidic clays, peroxides, halogens, vinyl chloride, and iodine pentafluoride.

Hazardous Decomposition Products: None.

Possibility of Hazardous Reactions: None

Section 11: TOXICOLOGICAL INFORMATION

Acute Effects

This product has been shown to have low oral toxicity (LD₅₀>5 g/kg) when tested on rats.

Chronic Effects

This product is not classified as a carcinogen by OSHA, IARC, ACGIH or NTP. This product has not been shown to produce genetic changes when tested on bacterial or animal cells. This product does not contain known reproductive or developmental toxins. Prolonged or repeated exposure can cause drying or dermatitis of skin.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: There is no information available at this time for this product. However, a spill may produce significant toxicity to aquatic organisms and ecosystems. Some studies have shown that certain bacteria and fungi have the ability to degrade terpenes, decreasing their toxicity to fish. When spilled, this product may act as an oil, causing a film, sheen, emulsion or sludge at or beneath the surface of a body of water.

Persistence/Degradability: Product is expected to be readily biodegradable.

Bioaccumulation/Accumulation: No appreciable bioconcentration is expected in the environment.

Mobility in Environment: Volatilizes rapidly.

Section 13: DISPOSAL CONSIDERATIONS

Disposal: Incinerate or dispose of in accordance with Local, State, and Federal Regulations.

Taking regulations into consideration, waste may be incinerated or handled through EPA Spill Control Plan via landfill or dilution. Commercially clean containers prior to disposal. Oil soaked rags should be disposed of properly to prevent spontaneous combustion. Hazardous substances cleaned with this product may create hazardous waste that should be properly characterized and disposed of in accordance with RCRA, state and local regulations.

Section 14: TRANSPORT INFORMATION

US DOT Shipping Classification

Proper Shipping Name: TERPENE HYDROCARBONS, N.O.S

Hazard Class: 3

Material Safety Data Sheet
FC-PRO Xylene Replacement

Identification No.: UN2319
Packing Group: III
Label/Placard: exception §173.150(f) applies.

TDG Status: Hazardous
IMO Status: Hazardous
IATA Status: Hazardous

The listed transportation classification does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptions.

Section 15: REGULATORY INFORMATION

Proposition 65: California Safe Drinking Water and Toxic Enforcement Act of 1986

This product is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65 at levels which would be subject to the proposition.

SARA Title III (Section 313)

This substance contains no materials subject to the reporting requirements of SARA Title III (Section 313).

Section 16: OTHER INFORMATION

NFPA 704: National Fire Protection Association

Health – 1 (slight hazard) Fire – 2 (moderate hazard) Reactivity – 0 (minimal hazard)

Legend

EPA – United States Environmental Protection Agency

IARC – International Agency for Research on Cancer

NIOSH – National Institute for Occupational Safety and Health

NTP – National Toxicology Program

OSHA – United States Occupational Health and Safety Administration

Caution: The user should conduct his/her own experiments and establish proper procedures and control before attempting use on critical parts.

Prepared by FC PRO Technical Team.

The information contained herein is based on current knowledge and experience: no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information obtained by the user. No warranty is expressed or implied regarding the accuracy of this data, the results to be obtained from the use thereof, or that any such use will not infringe any patent. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customers, and the protection of the environment. This information is furnished upon the condition the person receiving it shall determine the suitability for the particular purpose. This MSDS is to be used as a guideline for safe work practices and emergency response.